



Product Bulletin

SP-6

ROOF MOSS TREATMENT

DESCRIPTION:

ROOF MOSS CLEANER IS INTENDED FOR THE REMOVAL OF MOSS ON ROOFS, PATIOS, SIDEWALKS, ANYWHERE MOSS GROWS. IT IS NON-STAINING AND NON-CORROSIVE TO GALVANIZED GUTTERS. BE SURE TO COVER LAWN AND PLANTS AND KEEP PETS AWAY FROM OVER-SPRAY TO PREVENT COLLATORAL DAMAGE.

DIRECTIONS:

PREVENTATIVE TREATMENT: Remove as much moss as possible mechanically by sweeping or brushing the surface with a stiff bristle brush. Then:

1. Mix 1 part ROOF MOSS CLEANER to 4 parts water.
2. Apply with sprinkling can, hose-end sprayer, or tank sprayer. Thoroughly wet moss, using approximately 1 gallon of mixture to 100 sq. ft.
3. Repeat treatment as necessary, when new moss growth begins to appear.

FOR HEAVY MOSS GROWTH: Where it is impractical to first remove the moss prior to treatment:

1. Mix 1 part ROOF MOSS CLEANER to 4 parts water.
2. Apply at the rate of 3 gallons mixture to 100 sq. ft., thoroughly soaking the moss.
3. After moss turns brown, it can be removed by hosing, sweeping, or raking off the treated area.

TECHNICAL DATA:

pH CONCENTRATE.....	10.5
VISCOSITY.....	THIN LIQUID
COLOR.....	CLEAR FOAM
PROPERTIES.....	N/A
PERCENT SOLIDS.....	20%
DENSITY (LBS/GAL).....	N/A
SPECIFIC GRAVITY.....	1.2
RINSING.....	EXCELLENT
SOLVENT.....	N/A
SURFACTANTS.....	N/A
BIODEGRADABILITY.....	N/A

FOR FURTHER INFORMATION REFER TO THE MATERIAL SAFETY DATA SHEET

PACKAGING:

Available in 250 gallon totes, 55 gallon drums, 5 gallon pails and 4 gallon cases.

PRODUCT CODE:.....SP-6

MANUFACTURED FOR:



SINCE 1952 · PRESSURE WASHERS

· STEAM CLEANERS

· WASHWATER RECYCLING & FILTRATION SYSTEMS

2222 - 15th Avenue West
Seattle, WA. 98119

1 MILE SOUTH OF THE BALLARD BRIDGE
206-283-5252 / 800-863-7867

www.seattlepump.com