

### DIRECTIONS FOR USE

Use 2-8 ounces per gallon of water to remove stains caused by hard water, iron and other heavy metal contamination (rust), from tile and/or painted surfaces. Particularly rusty parts may call for use at full strength followed by flushing with water. Can be used to prepare bare metals prior to painting. Simply spray or brush on, let dry to a white residue and wipe off with a dry cloth.

### **FOR INDUSTRIAL USE ONLY**

MANUFACTURED FOR:  
**SEATTLE PUMP AND EQUIPMENT CO.**  
2222 15th Avenue West  
Seattle WA 98119  
1 MILE SOUTH OF THE BALLARD  
BRIDGE  
**206-283-5252 / 800-863-7867**

Net Contents: 1 Gallon (128 fl. oz.) **SP-38-01**



- PRESSURE WASHERS
- STEAM CLEANERS
- WASHWATER RECYCLING and FILTRATION SYSTEMS
- SOAPS, ACIDS, DEGREASERS, WASH MITTS and BRUSHES

[www.seattlepump.com](http://www.seattlepump.com)

## **RUST REMOVER PHOSPHATIZER**

**CONTAINS PHOSPHORIC ACID**

(COMPARE TO **OSPHO**)

AN ACIDIC SOLUTION DEVELOPED FOR REMOVING RUST STAINS ON PAINTED SURFACES (I.E. SHIP BULKHEADS). IT IS ALSO EFFECTIVE AS A METAL CLEANER AND PHOSPHATIZING AGENT IN PREPARATION FOR PAINTING.

### **CAUTION**

**DANGER:** Contains Phosphoric acid, & Ethylene Glycol Monobutyl Ether. Causes burns to eyes. May cause burns to skin. Harmful if swallowed. Avoid contact with eyes, skin, and clothing. Wear safety goggles, rubber gloves, and other suitable protective clothing when handling. Wash thoroughly after handling. Avoid breathing mist. **DO NOT** take internally. Before opening, relieve any pressure build-up in bottle by loosening cap slowly. Keep container closed when not in use. Avoid contact or mixing with chlorine releasing materials. Store away from heat and direct sunlight.

### **EMERGENCY PROCEDURES FOR CONTACT WITH**

Remove contaminated clothing. Call a Physician Immediately.

**INTERNAL:** Dilute the acid immediately. For each ounce of acid ingested give at least 3 quarts of milk (or water if milk is not available) and allow vomiting to occur. **DO NOT INDUCE VOMITING.**

**EXTERNAL:** Immediately flush with cold water for at least 15 minutes, paying particular attention under nails.

For further information refer to the  
**Material Safety Data Sheet**  
**KEEP OUT OF REACH OF CHILDREN**

<b>H HEALTH</b>	<b>2</b>
<b>F FLAMMABILITY</b>	<b>0</b>
<b>R REACTIVITY</b>	<b>0</b>

### **NOTE:**

Seller makes no warranty, expressed or implied as to the use of this material beyond label instructions. Buyer assumes all risk of use and/or handling of this material when such use is contrary to label instructions.